29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : PIRTEK AW ISO 46 P/N G50P46 HYDRAULIC OIL

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet	**Emergency telephone number** 1-800-VALVOLINE
Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509 United States of America SDS@valvoline.com	**Regulatory Information Number** 1-800-TEAMVAL **Product Information** 1-800-TEAMVAL

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Chemical nature : Static Accumulator

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-	72623-87-1	Asp. Tox. 1; H304	1.06

Based			

SECTION 4. FIRST AID MEASURES

General advice	:	No hazards which require special first aid measures.
If inhaled	:	If breathed in, move person into fresh air. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	:	Remove contact lenses. Protect unharmed eye.
If swallowed	:	Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways)
Notes to physician	:	No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Water spray
Foam
Carbon dioxide (CO2)
Dry chemical

Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	carbon dioxide and carbon monoxide Hydrocarbons
Specific extinguishing methods	:	Product is compatible with standard fire-fighting agents.
Further information	:	Standard procedure for chemical fires.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	:	Prevent further leakage or spillage if safe to do so.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
Other information	:	Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	:	Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.
Conditions for safe storage	:	Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	:	No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based	72623-87-1	REL	5 mg/m3 Mist.	NIOSH/GUIDE
		STEL	10 mg/m3 Mist.	NIOSH/GUIDE
		PEL	5 mg/m3 Mist.	OSHA_TRANS
		TWA	5 mg/m3 Mist.	ACGIH
		STEL	10 mg/m3 Mist.	ACGIH
		TWA	0.2 mg/m3 Inhalable fraction.	ACGIHLIS_P

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
Safety shoes
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Odour : No data available

Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	> 425 °F / 218 °C (1013.33 hPa)
Flash point	:	> 390 °F / > 199 °C Method: Cleveland open cup
Evaporation rate	:	1 Ethyl Ether
Flammability (solid, gas)	:	No data available
Flammability (liquids)	:	Static Accumulating liquid
Flammability (liquids)	:	
Upper explosion limit	:	6 %(V) Calculated Explosive Limit
Lower explosion limit	:	1 %(V) Calculated Explosive Limit
Vapour pressure	:	0.0133333 hPa (21.11 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8686 g/cm3 (15.56 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Thermal decomposition	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	42 - 50 mm2/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity
Not classified based on available information.
Components:
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based**:**
Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD 50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

Skin corrosion/irritation
Not classified based on available information.
Product:
Result: Repeated exposure may cause skin dryness or cracking.

Components:
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based**:**
Species: Rabbit

Result: Not irritating to skin

Serious eye damage/eye irritation
Not classified based on available information.
Product:
Remarks: Unlikely to cause eye irritation or injury.

Components:
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based**:**
Species: Rabbit
Result: Not irritating to eyes

Respiratory or skin sensitisation
Skin sensitisation: Not classified based on available information.
Respiratory sensitisation: Not classified based on available information.
Components:
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based**:**
Test Type: Buehler Test
Species: Guinea pig
Assessment: Does not cause skin sensitisation.

Germ cell mutagenicity
Not classified based on available information.
Carcinogenicity
Not classified based on available information.
Reproductive toxicity
Not classified based on available information.
STOT - single exposure
Not classified based on available information.
STOT - repeated exposure
Not classified based on available information.
Aspiration toxicity
Not classified based on available information.
Product:
No aspiration toxicity classification

Components:
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based**:**
May be fatal if swallowed and enters airways.

Further information
Product:
Remarks: No data available

Carcinogenicity:

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based**:**

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l
Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
Exposure time: 21 d
Test substance: WAF
Method: OECD Test Guideline 211

Persistence and degradability

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based**:**

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential

Components:

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant		no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : No SARA Hazards

SARA 313
Component(s)SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

HEAVY PARAFFINIC DISTILLATE	64742-54-7	90.00 - 100.00 %

New Jersey Right To Know

HEAVY PARAFFINIC DISTILLATE	64742-54-7	90.00 - 100.00 %
Lubricating Oils (Petroleum), C20-50,	72623-87-1	1.00 - 5.00 %

Hydrotreated Neutral Oil-Based

California Prop 65 Proposition 65 warnings are not required for this product based on the results of a risk assessment.



The components of this product are reported in the following inventories:

TSCA	:	On TSCA Inventory
DSL	:	All components of this product are on the Canadian DSL.
AUSTR	:	On the inventory, or in compliance with the inventory
ENCS	:	On the inventory, or in compliance with the inventory
KECL	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory

Inventories
AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information
Revision Date: 07/31/2016

NFPA:	HMIS III:
	 0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic

NFPA Flammable and Combustible Liquids Classification
Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :
ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the “International Air Transport Association” (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the “International Civil Aviation Organization”
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System